

# J43340 | E-CANVAS Matt 340

COATED FABRIC

## PRODUCT SPECIFICATION \*

|                          |                  |      |       |
|--------------------------|------------------|------|-------|
| Weight                   | g/m <sup>2</sup> | 340  | ± 25  |
| Thickness                | µm               | 380  | ± 25  |
|                          | mil              | 15.0 | ± 1.0 |
| Colour Elrepho UVO (D65) | L                | 94,7 | ± 1,0 |
|                          | a                | 0,0  | ± 1,0 |
|                          | b                | 1,1  | ± 1,0 |
|                          | delta b          | 1,6  | ± 1,0 |
| CIE whiteness (D65/10°)  |                  | > 0  |       |
| Opacity                  | %                | > 98 |       |

### Printability

Simplex printable

### Printing Technology

● Indigo printing systems

### Compatibility

HP Indigo mit One-Shot-Technologie

## KEY APPLICATIONS

### Wall Decoration

- Canvas on stretcher frames
- Photo
- Art reproduction

## BENEFITS & PROPERTIES

- Special designed E-CANVAS coating
- Deep blacks, vivid colours
- Printable with full HP Indigo production speed
- First real polycotton Canvas material with well-known HP Indigo print performance
- Instant dry
- Perfect stretching and framing performance
- High light fastness with HP Indigo ElektroInk
- Acid free
- High smudge and water resistance

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 06/2015