# W70606 | E-PHOTO® Lustre 190

# **RESIN-COATED PAPER WITH PRIMER**

# E-PHOTO®

#### **PRODUCT SPECIFICATION \***

Weight DIN EN ISO 536	g/m²	186	± 6
Thickness DIN EN ISO 534	μm mil	186 7.3	± 6 ± 0.23
Gloss BYK (60°) ISO 2813		30	± 5
CIE whiteness (D65/10°) min. ISO 2469		> 140	
Opacity min. ISO 2469	%	> 92	

#### **BENEFITS & PROPERTIES**

- Guaranteed look and feel of traditional photographic paper
- Excellent runnability
- Excellent toner adhesion
- Water and dirt resistance
- High whiteness
- No whitebreak, even without scoring
- High ageing resistance (200+ years tested by Wilhelm Institute of Research)
- Certified by HP Indigo
- Qualified for Xeikon 8000 series (more information: https://printmedia.xeikon.com)
- Certified for Konica Minolta AccurioPress C83hc
- Certified for Ricoh Pro C72210x and Rico Pro C9210
- FSC® Mix Credit (available on request)

# Printability

Duplex printable

# **Printing Technology**

- Indigo systems
- Dry toner systems

# Compatibility

Certified for HP Indigo. Qualified for Xeikon 8000 series.

#### Declaration

FSC® Mix Credit (Available on request)

# Certificates



WIR 200-years-permanence



HP Indigo Certified Media



HP Indigo Best Performing Substrate



### **KEY APPLICATIONS**

#### Photo Merchandise

- Photo books
- Photo prints
- Cooking books
- Menu cards
- Business cards
- Covers
- Business reports

# **Dirletighnsquality**ebrochures

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 02/2017

