W90506 | E-PHOTO® Lustre/Matt 225

RESIN-COATED PAPER WITH PRIMER



PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m²	222	± 6
Thickness DIN EN ISO 534	μm mil	212 8.3	± 6 ± 0.23
Gloss BYK (60°) ISO 2813		30	± 5
CIE whiteness (D65/I0°) min. ISO 2469		> 135	
Opacity min. ISO 2469	%	> 92	

BENEFITS & PROPERTIES

- Guaranteed look and feel of traditional photographic paper
- Excellent runnability
- Excellent toner adhesion
- Water and dirt resistance
- High whiteness
- No whitebreak, even without scoring
- High ageing resistance (200+ years tested by Wilhelm Institute of Research)
- Certified by HP Indigo
- FSC® mix credit (available on request)

Printability

Duplex printable

Printing Technology

Indigo systems

Compatibility

Certified for HP Indigo

Declaration

 $\mathsf{FSC}^{\circledR} \; \mathsf{Mix} \; \mathsf{Credit} \; (\mathsf{Available} \; \mathsf{on} \; \mathsf{request})$

Certificates



HP Indigo Certified Media



HP Indigo Best Performing Substrate



WIR 200-years-permanence

KEY APPLICATIONS

Photo Merchandise

- Photo books
- Photo prints
- Cooking books
- Menu cards
- Business cards and further more

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 04/2017

